

High Speed Dibbler



For more info & video visit www.agrinomix.com





Home

About Us

Products

Service

Parts

Search

Contact Us

OFFERING SYSTEMS FOR:

- Transplanting
- Soil mixing and distribution
- Plug tray fillers
- Integrated seeding lines
- Dispensers and fillers for flats and pots
- Plug grading and consolidation
- Planting lines for cuttings
- Watering booms
- Stationary / movable conveyors
- Custom automation
- Labeling equipment
- Rolling bench growing systems
- Rolling bench automation
- Vision grading and shipping systems
- 24 hr. technical assistance
- Installation & service

300 Creekside Drive Oberlin, Ohio 44074 Tel: 440-774-2981 1-800-354-3750 Fax: 440-775-2104 www.agrinomix.com



See Product Video









FEATURES

High speed – up to 2,800 containers per hour

Easily adjustable crank handle height adjustment

Quick changing for virtually any dibble configuration

Built-in controls for integrating into existing production lines

OPTIONS

Multi-use dibble plates Custom dibble pins

ELECTRICAL REQUIREMENTS

Choose between 120VAC, 1 Phase, or 208/230 VAC 1 Phase

Our High Speed Dibbler enables growers to dibble holes in pots and flats in order to obtain uniform placement and planting depth. Holes can be dibbled at speeds up to 2,800 containers per hour. The machine utilizes high speed pneumatics and precision controls to achieve such high speeds. The High Speed Dibbler is equipped with magnetic dibble pins that quickly attach to a metallic mounting plate for ultimate flexibility and quick changeovers. Hole locations are set by manually positioning dibble pins directly in the pot or tray. Then, using the built in hand crank, the dibble plate is lowered to allow the magnet in the base of each dibble to simply attach to the plate as they come in contact with it. In short, the High Speed Dibbler is a versatile machine, designed to meet the needs of today's high speed production lines that are often changed due to product mix.